

Thermo Scientific Model 48i-TLE Trace Level Enhanced Carbon Monoxide Analyzer

Gas filter correlation analyzer

The Thermo Scientific™ Model 48i-TLE Trace Level Enhanced Carbon Monoxide (CO) Analyzer utilizes gas filter correlation technology to measure the amount of carbon monoxide in the air from sub-ppb levels up to 100ppm.

- U.S. EPA Designated Method (RFCA-0981-054)
- Ethernet connectivity for efficient remote access
- Enhanced user interface with one button programming and large display screen
- Flash memory for increased data storage and user downloadable software
- Enhanced electronics design optimizes product commonality



The Thermo Scientific Model 48i-TLE analyzer is a single chamber, single photomultiplier tube design that measures only CO.

Dual range and auto range are standard features in this instrument. Because the instrument is operated continuously in the CO mode, the response time is less than 10 seconds.

Temperature and pressure correction are standard features. User settable alarm levels for concentration a wide variety of internal diagnostics are available from an easy to follow menu.

This state-of-the-art gas analyzer offers features such as an Ethernet port as well as flash memory for increased data storage and field upgradeability.

Ethernet connectivity provides efficient remote access, allowing the user to download measurement information directly from the instrument without having to be on-site.

Easily programmable short cut keys allow you to jump directly to frequently accessed functions, menus or screens.

The larger interface screen can display measurement information and status, while viewing menu and operational screens.



Thermo Scientific Model 48i-TLE Trace Level Enhanced Carbon Monoxide Analyzer

Thermo Scientific Model 48i-TLE Trace Level Enhanced Carbon Monoxide Analyzer

Preset Ranges	0-1, 5, 10, 20, 50, 100, 200, 500, 1000 ppm 0-1, 2, 5, 10, 20, 50, 100, 200, 500, 1000 mg/m ³
Custom Ranges	0-1 to 1000 ppm 0-1 to 1000 mg/m ³
Zero Noise	0.02 ppm RMS (30 second averaging time)
Lower Detectable Limit	0.04 ppm (30 second averaging time)
Zero Drift (24 hour)	< 0.1 ppm
Span Drift (24 hour)	+/- 1% full scale
Response Time	60 seconds (30 second averaging time)
Linearity	+/- 1% full scale
Sample Flow Rate	0.5 liters/min
Operational Temperature	Performance specifications based on operation within 20°-30° C C range (per U.S. EPA guidelines). Instrument may be safely operated over the range of 5°-40°C
Power Requirements	100 VAC, 115 VAC, 220-240 VAC +/-10% @ 300W
Size and Weight	16.75"(W) x 8.62"(H) x 23"(D), 55 lbs. / 425 mm (W) x 219 mm (H) x 584 mm (D), 25 kg
Outputs	Selectable Voltage, RS232/RS485, TCP/IP, 10 Status Relays, and Power Fail Indication (standard). 0-20 or 4-20 mA Isolated Current Output (<i>optional</i>)
Inputs	16 Digital Inputs (standard), 8 0-10 Vdc Analog Inputs (<i>optional</i>)

Ordering Information

Model 48i-TLE Trace Level Enhanced Carbon Monoxide Analyzer

Choose from the following configurations/options to customize your own Model 48i-TLE analyzer

1. Voltage options:

A = 120 VAC 50/60 Hz
B = 220 VAC 50/60 Hz
J = 100 VAC 50/60 Hz

2. Internal zero /span:

C = Internal zero / span valves w/zero air scrubber

3. Filter Wheel Purge:

P = Filter wheel purge set-up

4. Optional I/O:

A = No optional I/O (standard)
C = 0-20, 4-20mA current output - 6 channels, 0-10v analog input - 8 channels

5. Mounting hardware:

A = Bench mounting and Ears/Handles, EIA

Other options:

- Tefl on particulate filter
- Rack mounts
- Rear extender

Your Order Code: 48i-TLE - _ _ _ _ _

To maintain optimal product performance, you need immediate access to experts worldwide, as well as priority status when your air quality equipment needs repair or replacement. We offer comprehensive, flexible support solutions for all phases of the product life cycle. Through predictable, fixed-cost pricing, our services help protect the return on investment and total cost of ownership of your Thermo Scientific products.

For more information, visit our website at thermoscientific.com

© 2014 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

This product is manufactured in a plant whose quality management system is ISO 9001 certified.

USA

27 Forge Parkway
Franklin, MA 02038
Ph: (866) 282-0430
Fax: (508) 520-1460
customerservice.aq@thermofisher.com

India

C/327, TTC Industrial Area
MIDC Pawane
New Mumbai 400 705, India
Ph: +91 22 4157 8800
india@thermofisher.com

China

+Units 702-715, 7th Floor
Tower West, Yonghe
Beijing, China 100007
+86 10 84193588
info.eid.china@thermofisher.com

Europe

Takkebijsters 1
Breda Netherlands 4801EB
+31 765795641
info.aq.breda@thermofisher.com

Thermo
SCIENTIFIC

A Thermo Fisher Scientific Brand